

Sharp Signage Display

SHARP MULTISYNC® E509



The entry point for professional display solutions, the Sharp MultiSync® E9 Series is designed for modern business environments that need more than a consumer TV can offer.

- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment
- Standardised functionality – shares a common identity with the wider Sharp display portfolio, ensuring unified operation and remote device management, and consistent styling for a seamless user experience.
- Effortless plug-and-play signage – the integrated USB MediaPlayer enables native UHD content playback with auto-start functionality, delivering instant digital signage without the need for external hardware or content management systems.
- Flexible orientation – designed for both portrait and landscape installation, with uniform bezel width on all sides to ensure a clean, professional look in any configuration.

Specifications

Panel Data

Bezel Horizontal (mm)	11
Bezel Vertical (mm)	11
Panel Response Time (ms)	8

Key Specifications

Special Characteristics	USB Media Player, NaViSet Administrator 2, CEC Support, Powered USB-Port, HDMI ARC, Scheduler
Built in Speakers (W)	10 + 10
Remote Management Operating Time	True 16/7
Supported Image Format	Max. resolution 15360 x 8640, JPG (baseline, progressive, RGB, CMYK)

Resolution

Optimum Resolution	3840 x 2160 at 60 Hz
Supported Resolution	1920 x 1200, 1024 x 768 , 1280 x 1024, 1920 x 1080, 640 x 480, 1280 x 720, 1280 x 960, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1400 x 1050, 4096 x 2160

Additional Features

Colour Versions	Black Back Cabinet, Black Front Bezel
Safety and Ergonomics	UKCA, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, VCCI, RCM
Warranty	3 years warranty incl. backlight

Weights and Measures

Shipping Carton Dimensions (Width) mm	1253
Shipping Carton Dimensions (Height) mm	761
Shipping Carton Dimensions (Depth) mm	128
Shipping Weight (Kg)	13

Electrical

Power Consumption on Mode [W]	99 (shipping)
Power Supply	100-240 V, Internal Power Supply

Ergonomics

Landscape Dimensions (Width) [mm]	1120
Landscape Dimensions (Height) [mm]	641
Landscape Dimensions (Depth) [mm]	60

Display

Screen Size (inch)	50
Screen Size (cm)	126

Connectivity

Digital Output Control	HDMI, USB Type C LAN 100Mbit
------------------------	---------------------------------

Video Terminals

Control Terminals	RS232C, LAN
-------------------	-------------

Display Module Data

Panel Technology	VA with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Brightness (cd/m ²)	350
Contrast Ratio	4000:1
Pixel Pitch (mm)	0.285
Viewing Angle (°)	178
Colour Depth [bn]	1.07 (8bit + FRC)
Active Screen Area (H/V) mm	1095 x 616
Max. screen time	up to 16 hours of use per day
Response Time (typ.) [ms]	8

Power Supply and Operating Environment

Operating Voltage (ACV)	100-240
Frequency (Hz)	50-60
Via AC Adapter	True
Operating Voltage (DCV)	100-240
Operating Temperature (°C)	0 - 40
Storage Temperature (°C)	-20 - 60
Storage Humidity Min [%]	10
Storage Humidity Max [%]	80
Power Saving Mode (W)	< 2 (Networked Standby)
Battery	< 0.5 (ECO Standby)

Installation

Portrait Installation	True
Landscape Installation	True
Landscape	True
Portrait	True
Mounting (VESA mm)	200 x 200 (FDMI)
Mounting (Number of Points/Pitch)	4
Mounting Screw Specification (Size/Max Length)	M6

Accessories

Accessories	Feet, Wall mount, USB-C cable, Trolley
Shipping Content	Cable Clamps, Power Cable, Remote Control, 2 x AAA batteries, Setup Manual, Display

Green Features

Energy Efficiency	LED backlight technology, Energy consumption: 90 kWh/1000 h, Energy efficiency class: G
Ecological Standards	Energy Star 8.0

Mechanical

Bezel Width (Left/Right) [mm]	11
Bezel Width (Upper) [mm]	11
Bezel Width (Lower) [mm]	11

Connectivity (Control/Serial) Data

RS232C IN	9600
RS232C OUT	9600

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	24 - 75

Environmental Conditions

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Audio Terminals

Speaker Output (W RMS)	Internal 10W + 10W
------------------------	--------------------

Connectivity (Audio/Video) INPUT

Audio 3.5mm Jack	1
------------------	---

Projectors

Weight (kg)	9
-------------	---

Touch Interface Specification

Haze Level [%]	Pro 25
----------------	--------

PC-Input

Input Data	1 x USB 2.0 (MediaPlayer)
------------	---------------------------

