

50" Digital Signage Display

# Sharp / NEC MultiSync ME501

Ihr Weg zur digitalen Beschilderung.



- Modern and slim design – robust yet elegant allowing for an unobtrusive integration into any application and environment.
- Ease of use and operation – smart installation, operation and maintenance functionality ensures accurate performance over the entire lifetime of the display saving time, effort and resources.
- Effortless content playback – the integrated USB media player supports various image video file formats for effortless and standalone content playback.
- Secure remote management – control your devices remotely and securely using NEC NaviSet Administrator 2; proactively manage maintenance requirements saving time and resources.
- Future Ready Connectivity – featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.

# Technische Daten

## DISPLAY

|                                   |                                                             |
|-----------------------------------|-------------------------------------------------------------|
| Bildschirmtechnologie             | VA with Direct LED backlights                               |
| Native Auflösung (Pixel)          | 3840 x 2160                                                 |
| Diagonale (Zoll / cm)             | 50 / 125.7                                                  |
| Seitenverhältnis                  | 16:9                                                        |
| Helligkeit (cd/m2)                | 400                                                         |
| Kontrastverhältnis                | ≥ 8000:1                                                    |
| Reaktionszeit [ms]                | 8                                                           |
| Betrachtungswinkel (H/V) 0 CR> 10 | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |

## STROMVERSORGUNG UND BETRIEBSUMGEBUNG

|                                        |                          |
|----------------------------------------|--------------------------|
| Betriebsspannung (ACV) / Frequenz (Hz) | 100-240 V AC; 50 / 60 Hz |
| Leistungsaufnahme (W) (Betrieb MAX.)   | 85 shipping              |
| Betriebstemperatur (oC)                | 0 to 40                  |
| Feuchtigkeit (%)                       | 20 to 80                 |

## INSTALLATION

|                                         |                           |
|-----------------------------------------|---------------------------|
| Querformat                              | •                         |
| Hochformat                              | •                         |
| Montage (VESA/Anzahl Punkte/Abstand mm) | 4 holes; 400 x 400 (FDMI) |

## KONNEKTIVITÄT (AUDIO/VIDEO) AUSGANG

|                               |   |
|-------------------------------|---|
| Audio/Kopfhörer 3,5-mm-Buchse | 1 |
|-------------------------------|---|

## ZUBEHÖR

|                      |          |
|----------------------|----------|
| Fernbedienungssender | Yes      |
| Netzkabel            | Yes      |
| Befestigungskonsole  | Optional |
| Tischstativ          | Optional |

## ECKWERTE

|                                           |             |
|-------------------------------------------|-------------|
| Begrenzte Herstellergarantie (in Jahren). | 3           |
| Integrierte Lautsprecher (W)              | 10 W + 10 W |
| Power-Management                          | •           |
| Gehäusefarbe                              | Black       |
| Temperaturfühler                          | •           |

## MAßE UND GEWICHTE

|                                      |                      |
|--------------------------------------|----------------------|
| Bezel-Größe (L/R) mm                 | 14.9                 |
| Bezel-Größe (U/L) mm                 | 14.9                 |
| Produktabmessungen (B/H/T) mm        | 1,128.4 x 649 x 62.6 |
| Versandkarton-Abmessungen (B/H/T) mm | 1,298 x 860 x 224    |
| Produktgewicht ohne Stativ (kg)      | 17.3                 |
| Versandgewicht (kg)                  | 24.1                 |

## KONNEKTIVITÄT (AUDIO/VIDEO) EINGANG

|                     |   |
|---------------------|---|
| HDMI                | 2 |
| DisplayPort         | 1 |
| Audio 3,5-mm-Buchse | 1 |

## KONNEKTIVITÄT (STEUERUNG/SERIELLE DATEN)

|                |   |
|----------------|---|
| RS232C Eingang | 1 |
| LAN-Anschluss  | 1 |
| USB            | 1 |

