

Annex B1 - Product environmental attributes

Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable).
Additional information regarding each item may be found under P15.

Brand *	Sharp	Logo 
Company name *	Sharp Electronics Europe Ltd	
Contact information * e-mail address	environment@sharp.eu	
Internet site *	www.sharp.eu	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.	
Type of product *	MFP
Commercial name *	MX-3560N
Model number *	MX-3560N
Issue date *	28th, March, 2019
Intended market *	☐ Global ☒ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution
P12.1-P12.2 Ergonomic requirements.

Model number *	MX-3560N	Logo	
Issue date *	28th, March, 2019		

Product environmental attributes - Legal requirements		Requirement met		
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do comply with the current European RoHS Directive. (See legal reference and NOTE B1)	☒	☐	
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	☒	☐	
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorocarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.	☒	☐	
P1.4*	Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	☒	☐	
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	☒	☐	
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 µg/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5.	☒	☐	☐
P1.7*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): www.sharp.eu	☒	☐	☐
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference)	☐	☐	☒
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal reference)	☒	☐	☐
P2.3*	Batteries and accumulators are readily removable. (See legal reference)	☐	☐	☒
P3	Conformity verification & Eco design (ErP)			
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at (add link or e-mail address):	☐	☐	☒
P3.2*	The product complies with the Eco design requirements for energy-related products, (see legal reference). Required information is; ☐ given in item P15 or added to this document, ☐ available at (add URL):	☐	☐	☒
		☐	☐	☒
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0,01% (see legal reference and NOTE B1).	☒	☐	☐
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0,1% by weight (see legal reference).	☒	☐	☐
P4.3*	If the ink/toner formulation/preparation is classified as hazardous or contains a substance for which there are Community workplace exposure limits, the product/packaging is adequately labeled according to applicable regulations and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference). NOTE: The toner is not classified as hazardous.	☐	☒	☐
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	☒	☐	
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used (see legal reference).	☒	☐	☐
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	☒	☐	☐
P6	Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	☒	☐	☐

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	<i>MX-3560N</i>	Logo	
Issue date *	<i>28th, March, 2019</i>		

Product environmental attributes - Market requirements (See General NOTE GN below)		Requirement met		
- Environmental conscious design		Yes	No	n.a.
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.			
P7	Design			
	Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	☒	☐	☐
P7.2*	Plastic materials in covers/housing have no surface coating.	☒	☐	☐
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.	☒	☐	☐
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.	☒	☐	☐
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	☒	☐	☐
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	☒	☐	☐
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	☒	☐	☐
P7.8*	Upgrading can be done using commonly available tools	☒	☐	☐
P7.9.	Spare parts are available after end of production for: 7 years			☐
P7.10	Service is available after end of production for: 7 years			☐
	Material and substance requirements			
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: PC Material type: PC+ABS Material type: PET			
P7.12	Insulation materials of external electrical cables are PVC free.	☐	☒	☐
P7.13	Insulation materials of internal electrical cables are PVC free.	☐	☒	☐
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content.	☒	☐	☐
P7.15	Printed circuit boards, PCBs (without components) are low halogen: all ☐ PCBs > 25 g ☐ are low halogen as defined in IEC 61249-2-21. (See NOTE B2)	☐	☒	☐
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: (FR40)	☒	☐	☐
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive) ☐ , TBBPA (reactive) ☒ (See NOTE B3), Other; chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4:	☒	☐	☐
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: >FR(17)< or >FR(40)<	☐	☐	☐
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See NOTE B5)	☐	☐	☐
P7.20*	Postconsumer recycled plastic material content is used in the product (See NOTE B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as a percentage of total plastic by weight) is 0~1.0 %. or b) The weight of recycled material is g.	☒	☐	☐

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available;
see <http://www.ecma-international.org/publications/standards/Ecma-370.htm>

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	MX-3560N	Logo	SHARP
Issue date *	28th, March, 2019		

Product environmental attributes - Market requirements (continued)		Requirement met		
Item		Yes	No	n.a.

Material and substance requirements (continued)
--

P7.21*	Biobased plastic material content is used in the product (See NOTE B7): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is 0~0.1 %. or b) The weight of the biobased plastic material is g.	☒	☐	☐
--------	--	-------------------------------------	--------------------------	--------------------------

P7.22*	Light sources are free from mercury, i.e. less than 0,1 mg/lamp. If mercury is used specify: Number of lamps: and maximum mercury content per lamp: mg	☒	☐	☐
--------	---	-------------------------------------	--------------------------	--------------------------

P8 Batteries

P8.1*	Battery chemical composition: LiMnO2	☐
-------	---	--------------------------

P9 Energy consumption (See NOTE B8)
--

P9.1 For the product the following power levels or energy consumptions are reported:

Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard for modes and test method *	energy
Sleep mode for ENERGY STAR® Operational Mode (OM) products	W	W	W		☒
Standby/off mode for ENERGY STAR Operational Mode (OM) products	W	W	W		☒
TEC value for ENERGY STAR TEC products (TEC= Typical Energy Consumption)	kWh/week	kWh/week	2.0 kWh/week* *The above TEC value meets TEC Requirement of ENERGY STAR for Imaging Equipment Version 2.0 .	Energy Star (ver. 2.0)	☐
Maximum power consumption	W	W	1840 W		☐
Operating mode	W	W	890 W		☐
Ready mode	W	W	138 W		☐
Preheat mode	W	W	114 W		☐
Auto power shut-off mode	W	W	0.9 W		☐
Plug-in off mode	W	W	0.2 W		☐
External Power Supply Efficiency Level (International Efficiency Marking Protocol) * :					☒
Print/Scan Speed * : 35 images per minute				Color/Monochrome	☐
Default time to enter energy save mode: 11 minutes					☐
P9.2*	Information about the energy save function is provided with the product.				☒

P10 Emissions (See NOTE B8)

Noise emission – Declared according to ISO 9296
--

P10.1	Mode	Mode description	Declared A-weighted sound power level L_{wAd} (B)	Declared A-weighted sound pressure level L_{pAm} (dB)		
				Operator position ☐	Bystander positions ☒	
				Desktop ☐	(only if product is not operator attended)	
				or Desk side ☐		
	Idle	* <i>Ready</i>	* <i>2.8</i>	<i>18</i>		☐
	Operation	* <i>Operation</i>	* <i>7.2</i>	<i>54</i>		☐
	Other mode					
Measured according to: ☒ ISO7779 ☐ ECMA-74						
☐ Other (only if not covered by ECMA-74 with L_{pAm} measurement distance m)						

The product meets the acoustic noise requirements of the following voluntary program/s: **Blue Angel RAL-UZ 205** ☒ ☐ ☐

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available;
see <http://www.ecma-international.org/publications/standards/Ecma-370.htm>

Model number *	MX-3560N	Logo	
Issue date *	28th, March, 2019		

Product environmental attributes - Market requirements (continued)		Requirement met		
Item		Yes	No	n.a.
Chemical emissions from printing products (See NOTE B10)				
P10.2*	Test performed according to ECMA-328 Determination of Chemical Emission Rates from Electronic Equipment (ISO/IEC 28360) ☐ , other specify: Blue Angel RAL-UZ 171	☒	☐	☐
P10.3	Typical emission rate (operation phase) is (mg/h): Color/Monochrome			☐
	Electrophotographic devices: Ozone 1.4 / - Dust < LOD / - Styrene 0.0 / - Benzene 0.02 / - TVOC 3.4 / - (" < LOD " means less than limit of detection.)			☐
	Ink devices: Dust Styrene Benzene TVOC			☒
	Note: compliance with maximum emission rates in eco labels to be declared in P14.			
P11 Consumable materials for printing products				
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	☒	☐	☐
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN 12281.	☒	☐	☐
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	☒	☐	☐
P11.4*	The product is delivered to end-user with default auto-duplex enabled.	☒	☐	☐
P13 Packaging and documentation				
P13.1*	Product packaging material type(s): Paper / Cardboard weight (kg): 5.76 Product packaging material type(s): Plastic / EPS weight (kg): 0.36 Product packaging material type(s): Wood weight (kg): 8.15			
P13.2*	Product plastic primary packaging is free from PVC.	☒	☐	☐
P13.3*	For product primary corrugated fiberboard packaging, specify the contained percentage of minimum post-consumer recovered fiber content: 80 %			☐
P13.4*	Specify media for user and product documentation (tick box): Electronic ☒ , Paper ☒ , Other ☐			☐
P13.5	(Please only complete this item if paper documentation used) User and product documentation on paper media is chlorine-free: If Yes, please specify: Totally chlorine-free Elemental chlorine-free Processed chlorine-free	☒	☐	
P14 Voluntary programs:				
P14.1	The product meets the requirements of the following voluntary program(s):			
	ENERGY STAR®	Criteria version:	Date:	Product category:
	Eco-label: Blue Angel	Criteria version: RAL-UZ205	Date: 16 January 2018	Product category: Office Equipment with Printing Function
	Eco-label: Nordic Ecolabel	Criteria version: 6	Date: 9 June 2016	Product category: Imaging Equipment
P15 Additional information (See NOTE B11)				

NOTE B10 A Guidance document on Chemical Emissions is available;
see <http://www.ecma-international.org/publications/standards/Ecma-370.htm>

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1, P4.1
(EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7, P4.2
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances)	P1.3, 5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
"REACH" Regulation (1907/2006), annex VII	P1.10
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2.3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II)	P4.3
Regulation (EC) 1272/2008 (CLP Regulation)	P4.3, P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1