

MX-B468P

Highly productive entry-level black & white business printer.



- A4 black & white printer with speeds of up to 44ppm and true 1200 x 1200 dpi printing
- Easily configure and monitor vital system information via the 2.4-inch colour LCD
- Wireless connectivity enables easy access from mobile devices and flexible printer placement (option)
- Printing from mobile devices made easy with AirPrint
- Multi-layered security features keep information safe in the document, on the device, and over the network. Plus a range of embedded features strengthen the device against attacks
- Compact footprint with an expandable configuration with paper capacity of up to 2,000 sheets
- Trusted Platform Module (option) delivers authentication, system integrity checks, and encrypt
- Energy management features reduce power consumption in active use or sleep mode
- Versatile paper handling; supports a wide variety of paper including cardstock, envelopes and small media

Spécifications

GÉNÉRAL

Technologie	Laser
Vitesse de production N&B ppm (A4)	44
Format papier: min.-max.	A6 - A4
Grammage papier (g/m²)	60 - 216
Capacité papier: std. (feuilles)	350
Capacité papier: max. (feuilles)	2000
Mémoire standard (Mo)	512
Disque dur	OPT
Disque dur (Go)	128GB ISD
Recto verso	STD
Caractéristiques du secteur - courant alternatif local calibré (Hz)	220-240v
Consommation d'énergie (kW)	0.509
Dimensions (mm)	399 x 390 x 264
Poids (kg)	13.5

RÉSEAU SANS FIL

Réseau sans fil (standard / option)	OPT
Norme	IEEE802.11a / ac / b / g / n
Modes d'accès	Infrastructure Mode, Wi-Fi Direct
Sécurité	WEP, WPA PSK, WPA EAP, WPA2 PSK, WPA2 EAP, WPA3

IMPRIMANTE EN RÉSEAU

Résolution (dpi)	1200 x 1200
Interface Std	STD: USB2.0 10Base-T / 100Base-TX / 1000Base-T
OS supportés	Windows 8.1, 10, 11, Windows Server 2012R2, Server 2016, Server 2019, Server 2022, Mac OS 10.15, 11, 12
Langage de description de pages	PCL5e / PCL6 emulation, PostScript 3 emulation
Typos disponibles	94 fonts for PCL, 163 fonts for PostScript 3 emulation

CAPACITÉ TONER

Noir (pages à 5% de taux d'encrage)	31000
-------------------------------------	-------

