

Projectors

SHARP P701U PROFESSIONAL LCD LASER PROJECTOR



Quieter than the tick of a watch, the P701U operates unobtrusively, delivering impressive projection performance without any noise distraction whilst producing sharp, detailed visuals with consistent clarity even in well-lit environments.

- No filter service required – a completely sealed optical laser LCD engine allows a filter-free design. Brilliant colour brightness is maintained and servicing costs need no longer feature in your budget.
- Low Noise Level – with 22dB, the silent technology will not disturb your meeting.
- Future-proof input management – thanks to 4K@30 Hz input processing.
- No lamp replacement – up to 20,000 h maintenance free operation possible due to Laser Light Source.
- Risk Group 2 – because of the Risk Group 2 compliance, no prescribed safety precautions are necessary.

Specifications

Display Module Data

| | |
|----------------------------|---------------------|
| Native Resolution (Pixels) | 1920 x 1200 (WUXGA) |
| Aspect Ratio | 16:10 |
| Contrast Ratio | 3000000:1 |

Key Specifications

| | |
|--------------------------|---|
| Special Characteristics | NaViSet Administrator 2, Carbon Savings Meter |
| 24/7 Operation Certified | True |

Accessories

| | |
|------------------|--|
| Shipping Content | Power Cable, Remote Control, User Manual, Lens cap, Setup Guide, 2 x AAA batteries |
|------------------|--|

Green Features

| | |
|----------------------|----------------------|
| Ecological Standards | ErP compliant |
| Ecological Materials | Downloadable manuals |

Additional Features

| | |
|-----------------------|---------------|
| Safety and Ergonomics | RoHS, CE, ErP |
|-----------------------|---------------|

Projectors

| | |
|-------------------|---------------------------|
| Weight (kg) | 9 |
| Weight (g) | 700 |
| Lens Shift (H) | True |
| Lens Shift (V) | True |
| Keystone (manual) | True |
| Audio Terminals | Mini Jack (3.5 mm) In/Out |

Power Supply and Operating Environment

| | |
|----------------------------|--------|
| Operating Temperature (°C) | 5 - 40 |
| Storage Humidity Min [%] | 20 |
| Storage Humidity Max [%] | 80 |

Environmental Conditions

| | |
|------------------------------|----|
| Operating Humidity (min) [%] | 20 |
| Operating Humidity (max) [%] | 80 |

Electrical

| | |
|--------------|-----------|
| Power Supply | 100-240 V |
|--------------|-----------|

