

NEC U250X

Order Code: 60002965

NEC U250X 3D ready DLP Projector

Projectors with almost no shadow and glare greatly improve the use of interactive whiteboards in schools. The integrated 3D capability makes you ready for the next step towards the digital classroom. Peace of mind also with regards to the delivery of content is ensured by a large variety of analog and digital inputs. For mobile use on a cart the projector can also be used in desktop mode. The projector comes with an easy to install wall-mount to ensure the quality of the installation and offers compatibility to various height-adjustable solutions.

An ideal solution for educational and business use.

DELIVERING GENUINE BENEFITS

3D ready - future-proof DLP®-Link™ technology with 120Hz.

Almost no shadow and glare - thanks to ultra-short throwing distance.

Free tilting - for desktop use as well as ceiling and floor projection.

Great connectivity - due to numerous analog and digital connection terminals as well as network capability.

Wall-mount included - for quick and easy installation, compatible with height adjustable systems.



OUTSTANDING PERFORMANCE

- **High Brightness** - 2500 ANSI lumens
- **Ultra-Short Throw Ratio** - 0.377:1
- **Long Lamp Life** - up to 4000 hrs
- **Virtual Remote** for full control via VGA
- **Speaker** with 10W
- **Long Life Filter** for longer cleaning intervals



SPECIAL CHARACTERISTICS

3D ready, 6-segment Colour Wheel, Auto Power ON/OFF, BrilliantColor™ and VIDI technology, Free Tilt, Kensington security slot, Long Life Lamp, Manual vertical Keystone Correction ($V = \pm 15^\circ$), Manual Wall Color Correction, Off-Timer, Plug & Play, Quick-Start-/Quick-Power-Off Function, Security Bar, Virtual Remote Control



ECO Innovation Green one touch ECO and AV mute button

Energy Efficiency Intelligent Power Management; Reduced power consumption. Only 0.5W stand-by; Software scheduling

Ecological Materials 100% recyclable packaging; Downloadable manuals

Ecological Standards RoHs compliant; TCO certified; ErP compliant; WEEE

Technical Specification NEC U250X

IMAGE	
Display	1 x 1.4 cm (0.55") 2x LVDS DMD (Aspect Ratio 4:3)
Native Resolution	1024 x 768 (XGA)
Brightness ¹	2500 ANSI Lumen
Contrast Ratio ¹	2000:1
Lamp	230 W AC
Lamp Life [hrs]	2500 (4000 Eco Mode)
Lens	F= 2.71, f= 4.42 mm
Projection Factor	0.377 : 1
Projection Angle [°]	55.3
Projection Distance [m]	0.132 – 0.319
Screen Size (diagonal) [cm]	Minimum: 160 / 63"; Maximum: 216 / 85"
Zoom	Digital Zoom; Manual
Supported Resolutions	SVGA; SXGA; SXGA+; UXGA; VGA; WXGA; XGA
Frequency	Horizontal: 15–91.1 kHz (RGB: 31.35 kHz– 91.1 kHz); Vertical: 50 – 85 Hz (120 Hz: Only for 3D signal)
CONNECTIVITY	
RGB (analog)	Input: 2 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
HDMI™	Input: 1 x HDMI™ (Deep Color, Lip sync) with HDCP
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 2 x 3.5 mm Stereo Mini Jack; 1 x RCA Stereo for Video and S-Video Output: 1 x 3.5 mm Stereo Mini Jack
PC Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45
Video Signals	PAL; PAL60; NTSC; SECAM; NTSC 4.43; PAL-N; PAL-M
REMOTE CONTROL	
Remote Control	Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Freeze; Help Eco Mode; ID set; Picture Adjust; Picture Mode; Presentation and Mouse Control; Source Select
ELECTRICAL	
Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	300 max.; 244 Eco Mode; 3 Network Stand-By Mode; 0.5 Power Savings Mode
MECHANICAL	
Dimensions (W x H x D) [mm]	427 x 200 x 406 (without lens and feet)
Weight [kg]	6
Fan Noise [dB (A)]	29 / 33 (Eco / Normal)
ENVIRONMENTAL CONDITIONS	
Operating Temperature [°C]	5 to 35
Operating Humidity [%]	20 to 80
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80
OPTIONAL ACCESSORIES	
Optional Accessories	Lamp (NP19LP); Manual Height Adjustable Wall Mount NP01HWM; Mobile Motorized Wall Mount NP01HM; Motorized Height Adjustable Wall Mount NP01HW
ERGONOMICS	
Safety and Ergonomics	CE; ErP; TÜV GS; RoHS; TCO
Speakers [W]	1 x 10 (mono)
WARRANTY	
Projectors	3 years pan-European service
Lamp	6 months, max. 1000 hrs
SHIPPING CONTENT	
Shipping Contents	Projector; IR Remote Control with Batteries; Power Cord (3 m); VGA cable (3 m); Wall-mount kit NP01WK; Users Manual on CD-ROM; Quick Setup Guide

¹ Compliance with ISO21118-2005